HONXIN

Prodcuts

TUBULAR CHIPBOARD

DESCRIPTION

We adopt high grade wood materials and eco-friendly glue to produce tubular chipboard which is in conformity with standard of European Grade E1.





CHARACTERISTICS

Tubular chipboard reserves the properties of wood and gets rid of its deficiency such as shrink after drying while swelling after wet, and heavy in weight.It is an ideal eco-friendly replacement to solid wooden door core.



APPLICATIONS

The core of flat door and isolation board

ADVANTAGES

-Environmental Protection: Meet Environmental standards of European E1.

-Light in weight: Compared to solid wood, tubular structure can reduce the 60% weight of board.

-Easy to processing: easy to cut, connect, it can improve work efficiency, reduce labor intensity.

-Sound insulation: 40mm door made of tubular chipboard, whose insultation effect can up to 28db.

-Heat preservation: 40 mm door made of tubular chipboard is equal to a brick wall with 300mm.

-Stable in dimensions: Absorption thickness swellling<1.5%.

-Anti-impact: it can be up to 20kg/sqm.

SPECIFICATION (mm)

	24	28	30	33	34	38
2000x1250	●	●	●	●	●	●
2000x900				●		●
2100x900						●

Website:www.honxinwood.com

Email:larry@honxinwood.com